

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/050306 A1

(51) International Patent Classification⁷: **G02F 1/313**,
G02B 6/12, 6/293

(21) International Application Number:
PCT/EP2003/012328

(22) International Filing Date:
5 November 2003 (05.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **PIRELLI & C. S.P.A.** [IT/IT]; Via Gaetano Negri, 10, I-20123 Milano (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FACCIO, Daniele**, Franco, Angelo [IT/IT]; Pirelli Labs, Viale Sarca, 222, I-20126 Milano (IT). **GORNI, Giacomo**, Maria [IT/IT]; Pirelli Labs, V.le Sarca, 222, I-20126 Milano (IT).

(74) Common Representative: **PIRELLI & C. S.P.A.**; Via Gaetano Negri, 10, I-20123 Milano (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to the identity of the inventor (Rule 4.17(i)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL,

[Continued on next page]

(54) Title: TUNEABLE GRATING ASSISTED DIRECTIONAL OPTICAL COUPLER



(57) Abstract: A tuneable grating assisted directional optical coupler (10) to couple a transmission signal, comprises a first waveguide (1) including a first core (7) and a first cladding (4), the first waveguide having a first effective refractive index (n_1). The coupler (10) also comprises a second waveguide (2) including a second core (8) and a second cladding (3), the second waveguide having a second effective refractive index (n_2), different from the first effective index (n_1), and being in substantially close proximity to the first waveguide (1) in a predetermined region (L) to provide coupling there between. A periodic perturbation (12) is positioned in the coupling region (L) for causing the coupling to be wavelength selective for one given wavelength (λ), a function of the first (n_1) and/or the second (n_2) effective refractive index. Additionally, the second cladding (3) of the second waveguide (2) comprises a tuneable material and the first cladding (4) of the first waveguide (1) comprise a non-tuneable material.



SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.